

200S FUEL FILTERS



EQUIPCO[®]
INNOVATIONS IN FUEL HANDLING

www.equipco.com.au



There are multiple element options available for a range of applications



Cast Aluminium head with 25mm BSP threads and mounting bolt holes. Perfect for easy fitting in to pre existing systems

Easy spin on/off canister design allows quick, easy replacement/upgrade of old filters

Drain cock can be unscrewed to drain water from canister if there is a problem with condensation in your tank (200S-6710 element only)

DESIGNED TO MOUNT ON LARGE OVERHEAD STORAGE TANKS OR PUMPS

Your answer to gravity flow or pump applications with bulk storage tanks, the 200S series filters enable flows up to 134 LPM with Working Pressure max. 50 PSI.

Code	Size	Micron	Pressure Max	Flow Rate	Fluids
200S-6710-25	1" BSP	10 micron	50 PSI max	67 LPM	Diesel, petrol, ULSD, biodiesel.
200S-6710W-25	1" BSP	10 micron water absorbing	50 PSI max	94 LPM	Diesel, petrol, ULSD, ethanol blends up to 15%
200S-672-25	1" BSP	2 micron	50 PSI max	67 LPM	Diesel, ULSD, petrol, ethanol or methanol blends up to 15%.
200S-942W-25	1" BSP	2 micron water absorbing	50 PSI max	94 LPM	Petrol, 100% Biodiesel, diesel/Bio diesel blends up to 20%, ULSD
200S-13410-40	1½" BSP	10 micron	50 PSI max	134 LPM	Diesel, ULSD, petrol, ethanol or methanol blends up to 15%.
200S-13410W-40	1½" BSP	10 micron water absorbing	50 PSI max	188 LPM	Diesel, petrol, ULSD, ethanol blends up to 15%
200S-1342-40	1½" BSP	2 micron	50 PSI max	134 LPM	Diesel, ULSD, petrol, ethanol or methanol blends up to 15%.
200S-1342W-40	1½" BSP	2 micron water absorbing	50 PSI max	134 LPM	Petrol, diesel/Biodiesel blends up to 20%

Code	Element	Micron	Pressure Max	Flow Rate	Fluids
200S-6710	200S-CE	10 micron. Particulate	50 PSI max	67 LPM	Diesel, petrol, ULSD, biodiesel.
200S-6710W	70062	10 micron water absorbing. Hydrosorb	50 PSI max	94 LPM	Diesel, petrol, ULSD, ethanol blends up to 15%
200S-672	70819	2 micron. Particulate	50 PSI max	67 LPM	Diesel, ULSD, petrol, ethanol or methanol blends up to 15%.
200S-942W	70232	2 micron water absorbing. Hydroglass	50 PSI max	94 LPM	Petrol, 100% Biodiesel, diesel/Bio diesel blends up to 20%, ULSD