



Castrol GTX Professional 15W-40

Superior sludge protection for greater engine reliability

Description

Castrol GTX Professional is one of the world's most trusted engine oils.

It's more than just oil. It's liquid engineering that protects against problems, like sludge, that your engine faces every day.

Severe driving conditions such as every day stop-and-go/stop-start traffic, harsh weather conditions and extended drain intervals can all cause the build-up of a thick, tar-like substance called sludge.

You can't see this sludge build-up but it can damage your engine's performance and cause premature engine failure.

Castrol GTX Double Action formula cleans away old sludge and protects against new sludge formation better* than tough industry standards.

Help extend the life of your engine with Castrol GTX Professional.

* vs API SN limits

Application

Castrol GTX Professional 15W-40 is suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA A3/B4, API SN/CF or earlier specification 15W-40 lubricant.

Advantages

Castrol GTX Professional 15W-40:

- Contains anti-sludge formula that provides superior sludge protection
- Superior protection against viscosity and thermal breakdown
- Anti-wear additives that extend the life of your engine

Typical Characteristics

Name	Method	Units	Castrol GTX Professional 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.875
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.7
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6710
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	113
Viscosity Index	ASTM D2270	None	133
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% wt	0.9

Product Performance Claims

API SN/CF, ACEA A3/B4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Professional 15W-40

04 Jan 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz