



## Agri Grease Ultra

Replaces Castrol Agri Grease Plus

### Description

**Castrol Agri Grease Ultra** is a high performance grease developed for use in a wide range of farm and associated machinery applications. This includes cars, trucks, 4WD's, pumps etc.

### Application

**Castrol Agri Grease Ultra** has been proven in the field as a performer in severe duty applications.

The formulation has been engineered to provide protection of ball and roller bearings, especially onland/on-road, high load applications. It is also suitable for general chassis greasing, ball joints, C.V. joints and other plain bearing lubrication.

### Advantages

- One grease reduces inventory, saves money.
- One grease simplifies servicing, avoids misapplication.
- Resists water wash off.
- Contains corrosion inhibitors, protection between seasons.
- Very high melting point, maintains lubricity.

### Typical Characteristics

Name	Method	Units	Agri Grease Ultra
Appearance	Visual	-	Smooth & tacky
Colour	Visual	-	Dark Green
NLGI	-	-	2
Base oil kinematic viscosity at 40°C	ISO 12058	mm <sup>2</sup> /s	Calculated
Penetration, worked 60 Cycles	ASTM D217	1/10 mm	280
Dropping Point, Grease	ASTM D2265	°C	>260
Timken OK Load	ASTM D2509	kg	30
Oil separation	IP 121	%	2

The above data is typical and does not constitute a specification.

### User Advice

**Castrol Agri Grease Ultra** is a very high performance lithium complex grease and to obtain full benefits of this product do not mix it with other soap base greases.

Although **Castrol Agri Grease Ultra** is generally compatible with other lithium based greases, its superior performance will be diminished by mixing with other greases.

**Castrol Agri Grease Ultra** is **NOT** compatible with Bentone (clay) or Aluminium complex greases. Housings or grease ways should be either cleaned or flushed to remove old lubricant.

## Additional Information

### Health, Safety & Environment

**Castrol Agri Grease Ultra** is considered non-hazardous according to Worksafe. However, in line with safe handling practices, it is recommended that the handling instructions outlined in the Castrol Material Safety Data sheet be followed.

#### Spillage

**Small:** Soak up using an inert mineral adsorbent such as Castrol MOP S and dispose of in the appropriate manner.

**Large:** Corrective action usually dictated by individual company safety procedures. Immediate containment and subsequent removal is essential.

**Disposal:** Oily materials must not be allowed to enter groundwater, watercourses, sewerage or drainage systems. Refer to local Waste Disposal Authority for legal requirements.

#### Removal

**Bare Metal Surfaces:** Remove with Castrol solvent cleaners or water based degreasers.

**Hand Cleaning:** Use any of the Castrol range of hand cleaners; e.g. CareClean Plus.

**Other Surfaces:** Contact your local Technical Advice Line on 1300 557 998.

Agri Grease Ultra

04 May 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia  
Technical Advice Line 1300 557 998 Customer Service 1300 554 890  
[www.castrol.com.au](http://www.castrol.com.au) [www.msds.castrol.com.au](http://www.msds.castrol.com.au)