

RX SUPER 15W-40 CJ-4/E9

Castrol RX SUPER 15W-40 CJ-4/E9 is an advanced, heavy duty diesel engine oil. It is suitable for use in high speed 4- stroke diesel engines that use a broad range of fuel qualities. It is compatible with diesel engines fitted with EGR and the latest exhaust after treatment systems such as; DPF, DOC and/or SCR.

Recommended for use in all naturally aspirated and turbocharged diesel engines fitted in trucks, tractors, buses, LCV's and off-highway equipment, agricultural and fixed plant machinery.

FEATURES & BENEFITS

New and advanced Castrol RX SUPER 15W-40 CJ-4/E9 with specially engineered DuraShield™ Technology delivers 40% better wear protection*.

One of the main causes of damage in modern engines is abrasive wear. Castrol RX SUPER 15W-40 CJ-4/E9 with DuraShield™ Technology is proven in industry testing to provide protection to your engine in two ways:

- Under severe engine operating conditions soot can agglomerate to form large particles which displace oil on moving metal surfaces. This results in metal to metal contact. Castrol RX SUPER 15W-40 CJ-4/E9 with DuraShield™ Technology helps to prevent the agglomeration of soot as well as protecting surfaces from wear
- Castrol RX SUPER 15W-40 CJ-4/E9 with DuraShield™ Technology provides a protective layer on the moving metal surfaces which resists break down even under difficult conditions.

SPECIFICATION/APPROVALS

- ACEA E9
- API CJ-4
- JASO DH-2
- CAT ECF-3
- Cummins CES 20081
- DDC Powerguard 93K218
- Deutz DQC III-18 LA
- DTFR 15C100 (MB 228.31)
- Mack EO-O Premium Plus
- MTU Oil Category 2.1
- RVI RLD-3
- Volvo VDS-4

Suitable for use in agricultural applications where API CJ-4 or ACEA E9 is required.

Pack Size	5L	7L	20L	205L	1000L	Bulk
Item Code	3418278	3420723	3418280	3418279	3418281	3418283
Barcode	9310084030765	9310084031250	9310084030758	9310084030741	9310084030734	



*average of wear parameters in industry tests vs industry standard limits

The images shown are for illustration purposes only and may not be an exact representation of the product.