



Product Data

Castrol Syntrox Universal Plus 75W-90

Universal Fluid for manual transmissions and axles

Description

Castrol Syntrox Universal Plus 75W-90 is a full synthetic, multipurpose manual transmission and final drive lubricant. It may be used in synchronised manual transmissions and final drives/differentials of a wide range of vehicles (commercial vehicle, construction equipment, passenger cars) where API GL-4 or API GL-5 fluids are required and it carries a number of approvals.

Advantages

- A single product for transmissions and final drives reducing inventory and the potential for misapplication
- Excellent low temperature fluidity provides improved shift quality and wear protection in cold conditions and improves fuel efficiency.
- Superior high temperature stability and excellent wear protection even in the most arduous conditions prolongs equipment life and allows for extended drain intervals.
- Full compatibility with conventional mineral oils and seals allows this product to be used in a wide range of applications.

Typical Characteristics

Name	Method	Units	Syntrox Universal Plus 75W-90
Appearance	Visual	-	Clear & Bright
Density @ 15C, Relative	ASTM D4052	g/ml	0.867
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	15
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	104
Viscosity Index	ASTM D2270	None	154
Flash Point, PMCC	ASTM D93	°C	143
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	67,000
Pour Point	ASTM D97	°C	-51

Product Performance Claims

API GL-4/ GL-5/ MT-1
SAE J2360
MAN 341 Z2
MAN 342 S1
MB-Approval 235.8
Scania STO 1:1G, Scania STO 2:0A FS
ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A
Volvo Transmission Oil 97312-046
Eaton Transmissions (Europe) approved for 300.000 km drain

Additional Information

Syntrax Universal Plus 75W-90 is registered under the following ZF approval numbers: ZF001471

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Syntrax Universal Plus 75W-90
09 Sep 2021
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com