



2.0" Bore 1.25" Rod GT Cylinder

Part Code	Rod Size	Stroke inch	Closed		Open		Description	Buckle Load
			inch	mm	inch	mm		Tonne
GT20A02	1.25"	2	14.25	362	16.25	413	Maximum Pressure: 3000psi (207 bar)	60.60
GT20A04		4	16.25	413	20.25	514		39.15
GT20A06		6	18.25	464	24.25	616		27.25
GT20A08		8	20.25	514	28.25	718		20.06
GT20A10		10	22.25	565	32.25	819		15.42
GT20A12		12	24.25	616	36.25	921	Ports 9/16" UNO	12.19
GT20A14		14	26.25	667	40.25	1022		9.90
GT20A16		16	28.25	718	44.25	1124		8.19
GT20A18		18	30.25	768	48.25	1226		6.88
GT20A20		20	32.25	819	52.25	1327		5.87
GT20A24		24	36.25	921	60.25	1530	Pins 1"	4.42
GT20A30		30	42.25	1073	72.25	1835		3.07
GT20A36		36	48.25	1226	84.25	2140		2.26
GT20A42		42	54.25	1378	96.25	2445		1.73
GT20A48		48	60.25	1530	108.25	2750		1.37

Note: Consider rod buckle load and cylinder force on longer than 24" stroke.

Specifications subject to change without notice. Version Date: August 2023.

Extend Force at Max	Tonne	Retract Force at Max	Tonne
	4.28		2.61

