

NF10 CLEAR BOWL FILTERS



Cast Aluminium head with 25mm BSP threads for easy fitting in to pre existing systems

Clear bowl allows fuel to be seen while travelling through, allowing you to easily identify just how dirty or clean your fuel is, while also allowing you to spot any water in your system

Bowl easily unscrews from head to allow quick replacement of old elements

Fuel resistant Polycarbonate bowl

Drain cock can be unscrewed to drain water from bowl if there is a problem with condensation in your tank.

For petrol or diesel use.

NF10 CLEAR BOWL FUEL FILTERS ARE BUILT FOR GRAVITY AND PUMP APPLICATIONS

CLEAR BOWL FUEL FILTERS

Built to handle flows up to 60LPM.

NF10	1" Fuel filter. 10 micron replacement element.
NF10WB	1" Filter as above. 10 micron water absorbing element.
NF20	Replacement element to suit NF10 filter. 10 micron.
NF20WB	Element as above. Water absorbing properties to suit NF10WB.

Specifications

FLOW RATE	Up to 60 LPM.
PRESSURE	100 PSI Working Pressure.
MICRON SIZE	10

NF10

- 10 micron paper element.
- 1" female BSP inlet/outlet.
- 60LPM maximum flow rate.
- Up to 100 PSI working pressure.
- Clear bowl for visual checking of fluid.
- Drain cock for excess fluid.
- Removable head.
- Replaceable element.
- For petrol or diesel use.
- Product dimensions: 150mmL x 150mmW x 390mmH.