

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

PREMIER SAE 30 SG/CD

PRODUCT DESCRIPTION

Premier SAE 30 SG/CD is a well proven monograde engine oil for four stroke petrol (lawn mowers) and normally aspirated diesel engines. **Premier SAE 30 SG/CD** meets the API SG/CD Service Classifications. It provides improved protection resistance against engine wear, high temperature oxidation deposits to engines of older passenger cars and it is also recommended for veteran and vintage cars where high viscosity, low additive oils are required.

BENEFITS

A balanced combination of new type anti-wear additives imparts high film strength and low friction between all moving parts thereby minimising wear. Thermal degradation and decreased viscosity does not occur thereby ensuring positive full oil flow to all vital engine parts by the oil pump. The careful balance of anti-wear additives in relation to phosphorus levels minimises poisoning of the catalyst. Rust inhibitors overcome the rust prone condensation tendencies in cooling engines after engine shut-down.

SPECIFICATIONS

Premier SAE 30 meets the following demanding performance requirements:

API: SG/CD.

US Military Specification: MIL-L-46152B

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property		ASTM Method	Results
Appearance		Visual	Red
Density (kg/Lt)	@ 15°C	D-4052	0.878
Viscosity (cSt)	@ 100°C	D-445	11.75
	@ 40°C	D-445	105
Viscosity Index		D-2270	100
Pour Point (°C)		D-97	-21
Flash Point COC (°C)		D-92	228
TBN (mg KOH/g)		D-2896	5.3

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 5 Litres and 1 Litre.

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI1-2020

Effective: July 2019

MR917011/1





