

Section 1 - Identification of Chemical Product and Company

Premier One Products Pty Ltd
Unit 10, 11-13 Potter Close
Wetherill Park, NSW 2164

Phone: 02 9756 2419

Fax: 02 9756 2020

Email: sales@premieroneproducts.com.au

Chemical nature: Water solution of phosphoric acid and ammonium bifluoride.

Trade Name: Aluminium Brightener

Product Use: Aluminium cleaner.

Creation Date: October, 2016

This version issued: December, 2016 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. N, Dangerous to the environment. C, Corrosive. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S7

ADG Classification: Class 8: Corrosive Substances.

UN Number: 1760, CORROSIVE LIQUID, N.O.S. (Phosphoric acid, Ammonium bifluoride).



GHS Signal word: DANGER

Corrosive to metals Category 1

Acute Toxicity Oral Category 4

Acute Toxicity Dermal Category 4

Skin Corrosion /Irritation Category 1

Hazardous to aquatic environment Short term/Acute Category 3

HAZARD STATEMENT:

H290: May be corrosive to metals.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H402: Harmful to aquatic life due to extreme pH.

PREVENTION

P102: Keep out of reach of children.

P234: Keep only in original container.

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P310: Immediately call a POISON CENTRE or doctor/physician.

P321: Specific treatment (see Section 4 of this SDS).

P363: Wash contaminated clothing before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water then apply calcium gluconate gel.

SAFETY DATA SHEET



SAFETY DATA SHEET

Product Name: Aluminium Brightener

Page: 2 of 7

This revision issued: December, 2016

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P390: Absorb spillage to prevent material damage.
P370+P378: Not combustible. Use extinguishing media suited to burning materials. Water fog or fine spray is the preferred medium for large fires.

STORAGE

P405: Store locked up.
P406: Store in corrosive resistant container with a resistant inner liner.
P402+P404: Store in a dry place. Store in a closed container.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: White milky liquid.

Odour: No odour.

Major Health Hazards: causes burns, harmful by inhalation, in contact with skin, and if swallowed. Note: in this context, Hydrofluoric acid includes ammonium bifluoride.

Hydrofluoric acid burns are a unique clinical entity. Dilute solutions deeply penetrate before dissociating, thus causing delayed injury and symptoms. Burns to the fingers and nail beds may leave the overlying nails intact.

The vast majority of cases involve only small areas of exposure, usually on the digits.

Solutions of less than 7% may take several hours before onset of symptoms, resulting in delayed presentation, deeper penetration of the undissociated HF acid, and a more severe burn.

SWA has a publication available, and it can be found at

<http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/gm1989hydrogenfluoride>

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Phosphoric acid	7664-38-2	28	1	3
Ammonium bifluoride	1341-49-7	5	2.6	Peak
Butyl icinol	111-76-2	3-6	96.9	242
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Before using this product, obtain a supply of calcium gluconate gel and leave it in an unlocked medicine cabinet near where this product will be used.

Gently massage a liberal quantity of calcium gluconate gel if available or prepare at site by adding 10 mL of 10% calcium gluconate injectable solution to 30 mL of KY jelly or other water soluble gel. Do not use calcium chloride as it causes skin necrosis). Apply gel every 15 minutes and massage continuously until pain subsides and/or redness disappears or until medical attention becomes available. It is recommended the applier wear chemical protective gloves, (e.g. butyl rubber gloves).

Medical attention must be provided immediately.

SAFETY DATA SHEET

Issued by: Premier One Products Pty Ltd

Phone: 02 9756 2149

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



SAFETY DATA SHEET

Product Name: Aluminium Brightener

Page: 3 of 7

This revision issued: December, 2016

Exposure to low concentrations may be followed by a delayed onset of symptoms; seek immediate medical attention for all exposures to any concentration of hydrofluoric acid.

Inhalation: If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: If skin contact occurs, immediately remove contaminated clothing. Wash skin thoroughly under running water, then liberally apply calcium gluconate gel and contact the Poisons Information Centre urgently.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting; rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed. Seek urgent medical attention. Note comments above about calcium gluconate treatment.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire.

Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flash point: Does not burn.

Upper Flammability Limit: Does not burn.

Lower Flammability Limit: Does not burn.

Autoignition temperature: Not applicable - does not burn.

Flammability Class: Does not burn.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC, Viton, Nitrile. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the corrosiveness of this product, special personal care should be taken in any cleanup operation. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services.

Contaminated area may be neutralised by washing with weak or dilute alkali. Baking soda, washing soda and limestone are suitable. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

SAFETY DATA SHEET

Issued by: Premier One Products Pty Ltd

Phone: 02 9756 2149

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



SAFETY DATA SHEET

Product Name: Aluminium Brightener

Page: 4 of 7

This revision issued: December, 2016

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Phosphoric acid	1	3
Ammonium bifluoride	2.6	Peak
Butyl icinol	96.9	242

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC, Viton, nitrile.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	White Milky Liquid.
Odour:	No odour.
Boiling Point:	Approximately 100°C at 100kPa.
Freezing/Melting Point:	Below 0°C.
Volatiles:	Water component.
Vapour Pressure:	2.37 kPa at 20°C (water vapour pressure).
Vapour Density:	As for water.
Specific Gravity:	No data.
Water Solubility:	Completely soluble in water.
pH:	About 13
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	As for water.
Coeff Oil/water Distribution:	No data
Autoignition temp:	Not applicable - does not burn.

SAFETY DATA SHEET

Section 10 - Stability and Reactivity

Reactivity: Most strong acids react with inorganic and organic bases such as amines to form salts. They also react with many metals liberating hydrogen gas. These reactions are often rapid and sometimes liberate much heat. They can also decompose many organic materials such as esters, in a reaction called hydrolysis.

Conditions to Avoid: Keep containers tightly closed.

Incompatibilities: bases, zinc, tin, aluminium and their alloys.

Fire Decomposition: Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. May form oxides of phosphorus and other phosphorus compounds. May form hydrogen fluoride gas and other compounds of fluorine. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Phosphoric Acid	Conc \geq 25%: C; R34
• Skin corrosion - category 1B	
Ammonium Bifluoride	\geq 1%Conc<10%: C; R34; R22
• Acute toxicity - category 3	
• Skin corrosion - category 1B	
Butyl Icinol	No risk phrases at concentrations found in this product
• Acute toxicity - category 4	
• Acute toxicity - category 4	
• Acute toxicity - category 4	
• Eye irritation - category 2	
• Skin irritation - category 2	

Potential Health Effects

Inhalation:

Short Term Exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. If liquid enters nasal passages, it will cause pain and burn nasal membranes. Patients with inhalation burns may develop acute pulmonary oedema.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Concentrated hydrofluoric acid solutions cause immediate pain and produce surface burns similar to those produced by other common acids (e.g., erythema, blistering & necrosis). Pain typically is described as deep, burning, or throbbing and often is disproportionate to apparent skin involvement.

Solutions of less than 7% may take several hours before onset of symptoms, resulting in delayed presentation, deeper penetration of the undissociated HF acid, and a more severe burn.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is corrosive to eyes. It will cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring is likely.

Long Term Exposure: No data for health effects associated with long term eye exposure.

SAFETY DATA SHEET



SAFETY DATA SHEET

Product Name: Aluminium Brightener

Page: 6 of 7

This revision issued: December, 2016

Ingestion:

Short Term Exposure: Mild poisoning causes nausea, vomiting, diarrhoea and abdominal pain. Blood may be vomited. Severe poisoning causes shock, blurred vision, muscle spasm, shallow breathing and convulsions. Kidney failure may occur later.

Long Term Exposure: Intake of more than 6 mg of fluorine per day may result in fluorosis, bone and joint damage. Hypocalcemia and hypomagnesemia can occur from absorption of fluoride ion into blood stream.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Butyl Icinol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

Salts, acids and bases are typically diluted and neutralised when released to the environment in small quantities. However, until diluted or neutralised it will kill all aquatic organisms it contacts due to extreme pH.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to separate the contamination in some way. Only if neither of these options is suitable, we suggest that you contact a specialist disposal company to arrange disposal, but we recommend that it be neutralised in a controlled manner before disposal.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1760, CORROSIVE LIQUID, N.O.S. (Phosphoric acid, Ammonium bifluoride).

Hazchem Code: 2X

Special Provisions: 223, 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 8: Corrosive Substances.

Packing Group: III

Packing Instruction: P001, IBC03, LP01

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredients: Phosphoric acid, Ammonium bifluoride, Butyl icinol, are mentioned in the SUSMP.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number

SAFETY DATA SHEET

Issued by: Premier One Products Pty Ltd

Phone: 02 9756 2149

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



...High performance
cleaning products...

SAFETY DATA SHEET

Product Name: Aluminium Brightener

Page: 7 of 7

This revision issued: December, 2016

Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, December, 2016.

<http://www.kilford.com.au/> Phone (02)9251 4532

SAFETY DATA SHEET

Issued by: Premier One Products Pty Ltd

Phone: 02 9756 2149

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)