

PILOT 2

 PLATINUM

ANTI-FOG AND ANTI-SCRATCH PLATINUM COATING

Bollé Safety revolutionises eye protection with an innovation that meets all international standards, particularly EN166 option K and N. Platinum guarantees more safety, reliability and a comfortable fit.

Washable **, this permanent coating on both sides of the lens gives them a high scratch resistance and delays fogging.

In all circumstances and at every moment, PLATINUM provides the highest safety for eyes.

** Washing using soap and water.




89 g

Pilot 2 Its co-injected, ventilated frame guarantees unequalled adaptability and comfort.



bollesafety.com.au








+ PLATINUM COATING (P)

+ EXCELLENT FIELD OF VISION

+ PC/TPR TWIN/MATERIAL FRAME

+ ADJUSTABLE STRAP

+ FITS OVER PRESCRIPTION GLASSES

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
PILOT 2	 Clear	1679110	C10 & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/P
	 Smoke	1679112	C13 & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/P
	  CSP	1679118	C11 & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/P

LENS MARKING

P. This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

I. The letter 'I' signifies 'Medium Impact' approval.

O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

B. Manufacturer name

OCULAR LENS CATEGORY:

O. Range of luminous transmittance 80-100% (clear).

1. Range of luminous transmittance 43 -88% (CSP).

3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

Chemical splash protection
Cutting
Spraying
Dust protection
Acid and alkaline handling
Wood and metal work

MAIN MARKETS

Petro Chemical
Construction
Manufacturing
Paint
Automotive
Labs

LENSES

- Platinum Coating - A high performance anti-fog + anti-scratch coating system applied on both sides of Clear and Smoke lenses
- 100% UV 385 - Clear
- 100% UV 400 - Smoke

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **B-CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS

LENSES	PC - 2,1 mm - Curve 6
FRAME	PP + TPV
TEMPLES	Non Applicable
STRAP	Nylon
FOAM	No
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact and chemical splash protection. Resists a 6mm at 45 m/s.