

GUARDIAN STROBES

The Guardian range, made for materials handling and light commercial applications, synonymous with high reliability and economical pricing, has expanded further with the introduction of a sleek new mini L.E.D light box.

The ever growing range continues to offer exceptional durability and performance utilising high impact polycarbonate lenses and quality components that permit continuous long term use.

Multi-voltage circuitry is consistent across the range, with all strobes operating between 12-80 volts making them ideal for materials handling applications, whilst the light box utilises dual-voltage circuitry for 12 or 24 volt operations.

NB: Candela rating measured through clear lens.
Comparative L.E.D candela ratings based on visual comparison to traditional strobes



Potted electronics protects and extends circuitry life




LIGHT COMMERCIAL & MATERIALS HANDLING

PART No. / DESCRIPTION

85336A Single Flash Strobe Light (Amber) Flange Base 12-80 Volts

Features high impact polycarbonate lens and includes mounting bolts and gasket

Current draw: 0.3/0.05A
Flash rate: 60 (Single)
Candela seconds: 60




85374A L.E.D Quad Flash Strobe Light (Amber) Flange Base 12-80 Volts

Current draw: 0.2A
Flash rate: 80 (Quad)
Comparative L.E.D candela rating: 60

85337A Single Flash Strobe Light (Amber) with Magnetic Base, Cigarette Lighter Plug and 2.5m Spiral Lead, 12-80 Volts

Features high impact polycarbonate lens
Current draw: 0.3/0.05A
Flash rate: 60 (Single)
Candela seconds: 60



85375A L.E.D Quad Flash Strobe Light (Amber) with Magnetic Base, Cigarette Lighter Plug and 2.5m Spiral Lead, 12-80 Volts

Current draw: 0.2A
Flash rate: 80 (Quad)
Comparative L.E.D candela rating: 60



GUARDIAN STROBES




PART No. / DESCRIPTION

85338A Single Flash Strobe Light (Amber) Flange Base 12-80 Volts

Features high impact polycarbonate lens and includes mounting bolts and gasket

Current draw: 0.3/0.05A
Flash rate: 60 (Single)
Candela seconds: 60




85368A L.E.D Quad Flash Strobe Light (Amber) Flange Base 12-80 Volts

Current draw: 0.2A
Flash rate: 80 (Quad)
Comparative L.E.D candela rating: 60

85339A Single Flash Strobe Light (Amber) with Magnetic Base, Cigarette Lighter Plug and 2.5m Spiral Lead, 12-80 Volts

Features high impact polycarbonate lens
Current draw: 0.3/0.05A
Flash rate: 60 (Single)
Candela seconds: 60




85369A L.E.D Quad Flash Strobe Light (Amber) with Magnetic Base, Cigarette Lighter Plug and 2.5m Spiral Lead, 12-80 Volts

Current draw: 0.2A
Flash rate: 80 (Quad)
Comparative L.E.D candela rating: 60

85340A Single Flash Strobe Light (Amber) Flange Base 12-80 Volts

Features high impact polycarbonate lens and includes mounting bolts and gasket

Current draw: 0.3/0.05A
Flash rate: 60 (Single)
Candela seconds: 60



85346A L.E.D Quad Flash Strobe Light (Amber) Flange Base 12-80 Volts

Current draw: 0.2A
Flash rate: 90 (Quad)
Comparative L.E.D candela rating: 60

