

ÕÕ

## 18V 125mm (5") Random Orbit Sander

Tnakita

Makitå



## **Product Statement**

#### 18V 125mm (5") Random Orbit Sander

The 18V LXT125 mm (5") Random Orbit Sander is designed for efficient sanding with three speed settings for quick material removal. It offers up to 40 minutes of runtime on low speed and 20 minutes on high speed per charge (BL1830B). The sander features a 2.8 mm random orbit action for fast, swirl-free finishing, and includes a one-touch electronic speed control switch for easy adjustment.

Built for comfort, it has an ergonomic body and grip, a pad brake for improved finish quality, and an efficient dust collection system. Durable components like a dust-sealed switch and bearing, along with oversized sealed-ball bearing construction, ensure longevity. Compatible with Makita vacuum cleaners, it uses 125 mm (5") hook-and-loop abrasive paper and includes a battery protection circuit for extended tool life.



## **Product Overview**





# **Product Specification Sheet**





| Abrasive paper size   | 125mm (5")              |
|-----------------------|-------------------------|
| Pad size              | 123mm                   |
| Orbits per minute     | 7,000/9,500/11,000opm   |
| Orbit diameter        | 2.8mm                   |
| Sanding strokes       | 14,000/19,000/22,000spm |
| Overall length        | 175mm                   |
| Skin weight           | 1.1kg                   |
| Weight (with battery) | 1.7kg (BL1830B)         |
| Voltage               | 18V                     |

- **3 stage speed control** push button control allows for 3 stage speed control in order to optimise the operating speed according to the finish requirements
- **Compact Design** redesigned with a lower center of gravity for improved handling and maneuverability during extended tasks
- **High power** powerful motor with high output, matching the power of the AC model for high efficiency in material removal
- **Ergonomically contoured grip** ergonomic grip design for comfortable use single handed, contoured to the palm of your hand for comfortable use in prolonged applications
- **Dust box** includes a standard dust box for efficient dust extraction during sanding, ensuring enhanced user safety
- Vacuum Compatible -the extraction port can connect to a dust extraction system for optimal dust removal efficiency
- Hook & loop fastening compatible with use of both hook and loop style sanding sheets
- **Brake Pad** engineered to minimize free spin, enhance overall finish, and reduce the risk of injury to the user and damage to the material

## Advantages



#### Power



Large 2.8mm orbit action engineered for efficient sanding

Control



Electronic 3 stage speed control for optimised control of finish requirements

#### Comfort



Compact and ergonomically designed for comfortable handling, ensuring ease of use

#### **Dust Extraction**



Self dust collection with supplied box or compatible with dust extractor

## Advantages



#### **Base Compatibility**

The DBO180 features a quick-change system compatible with 125 mm (5") (8hole) hook-and-loop abrasive paper, facilitating efficient pad changes for uninterrupted workflow.

This model includes interchangeable sanding pads, such as sponge, wool, and felt accessories, enabling versatile sanding operations across wood, metal, and other materials. From intricate detailing to larger projects, the DBO180 delivers precise results with reliability and efficiency, making it an ideal choice for professionals.



# **S**Our Range



|                       | DBO381 DBO480                                       |  | DBO180   | DBS180           |
|-----------------------|---|--|--|------------------|
|                       |   |  |  |                  |
| Abrasive paper size   | 125mm   | Hook & Loop Type: 114 x 102mm<br>Clamp Type: 140 x 114mm | 93 x 228mm   | 9mm              |
| Pad size              | 123mm   | 112 x 102mm  | 93 x 228mm   | 9 x 533mm        |
| Orbits per minute     | High: 11,000opm<br>Med: 9,500opm<br>Low: 7,000opm   | High: 14,000opm<br>Low: 11,000opm                        | High: 12,000opm<br>Med: 8,000opm<br>Low: 4,000opm  | 600 - 1,700m/min |
| Orbit diameter        | 2.8mm   | 1.5mm  | 2.0mm  | -                |
| Sanding strokes       | High: 22,000spm<br>Med: 19,000spm<br>Low: 14,000spm | High: 28,000spm<br>Low: 22,000spm                        | High: 24,000spm<br>Med: 16,000spm<br>Low: 8,000spm | -                |
| Overall length        | 175mm   | 171mm  | 336mm  | 500mm            |
| Skin weight           | 1.1kg   | 1.1kg  | 1.6kg  | 1.5kg            |
| Weight (with battery) | 1.7kg   | 1.7kg (BL1860B)  | 2.2kg (BL1860)                                     | 2.1kg            |
| Voltage               | 18V   | 18V  | 18V  | 18V              |

## Accessories



| Standard Accessor | ries  |   | Optional Accessories                              | 5        |   |
|-------------------|---|---|---|----------|---|
|                   | 794544-7<br>(For Re-order<br>D-54536 (10PK) | 125mm Aabrasive Disc – (120<br>Grit 1x) |   | -        | <u>125mm Random orbital Sander</u><br><u>Discs – Economy Grade</u><br>For wood sanding 40- 320 grit<br>(10PK)   |
|                   | 135246-0                                    | Dust Box                                | makita<br>e b e b e b e b e b e b e b e b e b e b | _        | <u>125mm Random orbital Sander</u><br><u>Discs – Standard Grade</u><br>Aluminum Oxide + Zinc Stearate<br>40- 400 Grit (10Pk)<br>Aluminum Oxide + Zinc Stearate<br>40- 400 Grit (50Pk) |
| Optional Accessor | ies   |   | Thakita   |          | Aluminum Oxide 40- 400 Grit<br>(10Pk)<br>Aluminum Oxide 40- 400 Grit<br>(50Pk)  |
|                   | 197468-0                                    | 123mm Sanding Pad Hook &<br>Loop        |   | -        | Sanding & Polishing Accessories<br>(Hook & Loop)<br>Sponge Pad<br>Wool Pad<br>Felt Pads<br>Hard/Soft polishing Discs  |
|                   | 794560-9                                    | 140mm Wool Pad Hook<br>Loop             |   | 194746-9 | Paper Dust Bag – (5PK)  |

# **Extraction System**

| Model   | Applicable Cuffs                         | Hose                              | Vacuum                   |  |
|---------|--|-----------------------------------|--------------------------|--|
|         | 22mm Power Tool Adaptor – W107418661     |                                   | VC2012L                  |  |
| Trakita | 22mm Quick Fit Tool Adaptor - W107418678 | 32mm Quick Fit Hose – P-<br>84084 |                          |  |
|         | 24mm Quick Fit Adaptor– P-70378          |                                   | VC3012L (Quick fit Hose) |  |
|         | 24mm Rubber Power Tool Adaptor – P-81745 | Hose Complete<br>P-81739          | VC4210L                  |  |