

Product Objectives

- Designed to suit the needs of a wide range of users for cutting and grinding applications with a new quick change tool-less wheel change system
- Develop a brushless 125mm angle grinder with the new X-Lock wheel change system. Fasten the wheel with just one click and easy removal by pulling the release lever



Product Overview



Product Specification Sheet



125mm (5")
3,000 - 8,500rpm
396mm
2.5kg
3.1kg
18V

- X-Lock tool-less wheel lock system allows the installation / removal or X-Lock wheels in just a single action. Minimising down time and preventing over of under tightening of accessories
- eXtreme Protection Technology provides enhanced protection against dust and moisture, ensuring the longevity of the tool
- Active Feedback Sensors shuts down the tool in the event of a kickback
- Variable speed control dial allows speed to be adjusted from 3,000rpm to 8,500rpm in order to correctly match the speed to the accessory and the application
- Anti Restart safety protection not allowing accidental start-up should the battery be installed while the trigger is engaged
- Automatic Torque Drive adjusts speed and torque for optimal performance. During operation, if the tool is put under heavy load, ATD detects the added demand and applies more torque to finish the job
- Electric brake maximised safety and productivity by rapidly slowing the wheel after the trigger has been released

Advantages

Performance



High Powered 18V Brushless Motor

Control



Variable speed control dial 3,000 – 8,500rpm

Innovation



X-Lock Tool-less wheel change

Safety



Active Feedback sensors, Anti-restart Electric brake & Soft start

Advantages



Our Range

	DGA504	DGA505	DGA506	DGA508	DGA511	DGA512	DGA517	DGA518	DGA519
Switch type	Slide	Paddle	Slide	Paddle	Slide	Slide	Paddle	Paddle	Paddle
Wheel diameter	125mm (5")	125mm (5")	125mm (5")	125mm (5")	125mm (5")				
No load speed	8,500rpm	8,500rpm	8,500rpm	8,500rpm	3,000 - 8,500rpm	3,000 - 8,500rpm	3,000 - 8,500rpm	3,000 - 8,500rpm	3,000 - 8,500rpm
Overall length	362mm	362mm	362mm	362mm	382mm	382mm	382mm	382mm	396mm
Skin weight	2.0kg	2.0kg	2.0kg	2.0kg	2.5kg	2.5kg	2.5kg	2.5kg	2.5kg
Weight (with battery)	2.6kg	2.6kg	2.6kg	2.6kg	3.1kg	3.1kg	3.1kg	3.1kg	3.1kg
Voltage	18V	18V	18V	18V	18V	18V	18V	18V	18V
Electric brake	No	No	Yes	Yes	No	No	Yes	Yes	Yes
Variable speed	No	No	No	No	Yes	Yes	Yes	Yes	Yes
AWS	No	No	No	No	No	Yes	No	Yes	No
X-Lock	No	No	No	No	No	No	No	No	Yes

Accessories

Standard Accessories						
XLOCK STORY	E-00402	125mm X-Lock grinding disc				
Tnakita.	158237-4	Side Grip				



Optional Accessories						
Trakila XLOCK	E-00418	X-LOCK 125 x1.2x22.23 Flat Inox Cutting Disc 1 Piece / A60T Grit				
LOCK	E-00393	X-LOCK 125 x6x22.23 Metal Grind Disc 1 Piece / A36P Grit				
THATTA LOCK	E-00402	X-LOCK 125 x6x22.23 Inox Grind Disc 1 Piece / WA36N Grit				
makita	191G05-4	X-LOCK 125mm Plunge Diamond Wheel Guard Aluminum Housing / Able To Plunge Cut (Available April)				
Thakita.	E-02076	X-LOCK 125mm Segmented Diamond Blade (Available February)				