

**Makita**

# 230mm (9") Angle Grinder

**240v**

GA9081X1



## 230mm (9") Angle Grinder

The 230mm (9") angle grinder (GA9081X1) has a high performance 2,400-watt motor for heavy duty applications. The GA9081X1 features anti-restart protection, this means the motor will not restart after a power disruption if the switch remains in the on position, users can release and reengage the two-stage trigger switch to restart the unit.

The built-in soft start module will reduce initial start-up shock, allowing the user to better control the unit while it achieves full power. The GA9081X1 also comes standard with a vibration proof rubberised side grip that has been positioned to enhance maneuverability, balance, and help minimise user fatigue.



# Product Overview

**240V**

Soft Start

Torque Limiter

Anti-Restart Protection

High Performance 2,400W Motor

Two Stage Trigger Switch

Vibration Proof Side Grip



# Product Specification Sheet

240V



Wheel Diameter	230mm (9")
Hole Diameter	22.23mm
Spindle Thread	M14
No Load Speed	6,600rpm
Continuous Rating Input	2,400W
Overall Length	461mm
Net Weight	6.3kg
Power Supply Cord	2.0m

- **Soft Start** – When the trigger is pressed the wheel will start slowly to reduce initial start up shock, then rapidly accelerate to maximum speed.
- **Torque Limiter** – Limits the power at start-up and during heavy duty applications to protect the mechanical components.
- **Anti-Restart Protection** – If there is a power disruption and the switch remains in the on position the tool will not restart until the user releases and reengages the two-stage trigger switch.
- **High Performance 2,400W Motor** – Features a powerful 2,400-watt motor for industrial applications.
- **Two-Stage Trigger Switch** – The switch requires two stages of action before the tool will start, this helps avoid accidental operation. The tool will shut down if the user releases the trigger switch and will need to be reengaged.
- **Vibration Proof Side Grip** – The inclusion of a vibration proof side grip allows users to better control the tool ergonomically.

## Performance



2,400-Watt motor allows for continuous heavy-duty operation.

## Safety



Anti-restart protection and soft start to enhance user safety.

## Durability



Engineered for increased durability and longer tool life.

## Comfort



Vibration proof side grip minimises user fatigue.



# Our Range

240V





Wheel diameter	230mm (9")						
No Load Speed	6,600rpm						
Continuous Rating Input	2,400W	2,400W	2,400W	2,400W	2,400W	2,200W	2,200W
Active Feedback Sensing Technology (AFT)	✗	✓	✓	✗	✗	✗	✗
Brake System	✗	Mechanical Brake	Mechanical Brake	✗	✗	✗	✗
Anti-Restart	✓	✓	✓	✓	✗	✓	✗
Soft Start	✓	✓	✓	✓	✗	✓	✗
Anti Vibration Housing	✗	✓	✓	✓	✗	✗	✗
Vibration Proof Grip	✓	✓	✓	✓	✓	✓	✗
Handle Type	Straight Handle	Straight Handle	D-Handle	Straight Handle	Straight Handle	D-Handle	Straight Handle
Overall Length	461mm	506mm	506mm	509mm	511mm	450mm	450mm
Net Weight	6.3kg	6.3kg	6.4kg	6.5kg	5.1kg	5.8kg	5.5kg




## Standard Accessories

	194543-3	Vibration Proof Grip
	782034-2	Lock Nut Wrench 35

## Optional Accessories

	224256-3	Outer Flange 78
	224257-1	Inner Flange 78

## Optional Accessories

	122913-6	230mm Cutting Guard
	198379-2	230mm Dust Collecting Wheel Guard Plunge
	<a href="#">Link to Website</a>	Grinding Wheels
	<a href="#">Link to Website</a>	Cutting Wheels
	<a href="#">Link to Website</a>	Diamond Cutting Wheels