POWEREASE P SHAFT (C1)



SKU: 166 R225-RP

Features

- The Powerease R225 is a 223 cc (13.6 cu-in) singlecylinder air-cooled 4-stroke internal combustion generalpurpose gasoline engine with a horizontal shaft.
- The Powerease R225 engine has an OHV design; flat suction valve carburetor; recoil starter or electric starter, transistorized magneto ignition (TCI) system and centrifugal mechanical governor system.
- A 70.0 mm (2.76") cylinder bore and 58.0 mm (2.28") piston stroke give the Rato R225 motor a total of 223 cc of displacement. The compression ratio rating is 9.0:1. It produced 7.5 hp of horsepower at 3,600 RPM and 13.0 N·m (1.33 kg·m, 9.58 ft·lb) of torque at 2,500 RPM.
- 7.5 hp
- Recoil /Electric Start
- 3/4" Keyed Shaft

Specifications

- Model: R225
- Type: 4-stroke, OHV, single cylinder
- Displacement: 223 cm 3 (13.6 cu-in)
- Shaft: 3/4" Keyed
- Max. horsepower: 7.5 hp at 3,600 RPM
- Max. torque (crank PTO): 13.0 N·m (1.33 kg·m, 9.58 ft·lb) at 2.500 RPM
- Carburettor: Flat suction valve carburetor
- Cooling system: Forced-air
- Ignition system: Transistorized magneto ignition (TCI)
- Lubricating system: Splash
- Starting system: Recoil / electric starter
- Stopping system: Ignition primary circuit ground
- **Fuel used**: Unleaded gasoline (octane number 86 or higher)
- **PTO shaft rotation**: Counterclockwise (from PTO shaft side)





POWEREASE P SHAFT (C1)



