



Nothing but **HEAVY DUTY.**™

## Product Information Document

### Overview

Customer Facing Name:	Rotary Detector 610m
Material Number:	RD600

### Product Overview



The MILWAUKEE® Rotary Detector 610m detects the red laser line up to 610m (diameter) for quick and easy elevations. Its durable rubber over-mold housing allows it to withstand drops up to 2m. With its built-in strobe protection, it reduces interference from other light sources on the jobsite which ensures a consistent and accurate readout. The Rotary Detector 610m also features an easy-to-read backlit display, making it more visible for any application. The Rotary Detector 610m is compatible with the M18™ Horizontal Rotary Laser 610m (2000') Red (M18RL610).

### Features and Benefits

- For use with M18™ Horizontal Rotary Laser 610m (2000') Red (M18RL610)
- 610m (diameter) working range
- 5 accuracy settings from 0.5mm to 5mm
- 4 different digital readout settings (Metric, Inches Decimal, Inches Fractional and Feet (10ths))
- Withstands 2m drops
- Reduces Interference with strobe light protection
- Adjustable audio: High, Low, Off
- Easy read backlit display
- IP67 rated protection

### Specifications

<b>WORKING RANGE WITH M18RL610</b>	610m (Diameter)
<b>IP RATING</b>	IP67
<b>DROP RATING</b>	2m
<b>RUN TIME</b>	40 Hours
<b>WEIGHT</b>	0.36kg
<b>WARRANTY</b>	3 Years

### Product Includes

Format - (qty) Customer facing name (model number)

- (1) Rotary Detector 610m (RD600)
- (1) Detector Clamp
- (2) AA Batteries

### Unique Selling Points

### Additional Notes

Related Accessories (Material Number)	
Related Products (Material Number)	M18RL6100C, M18RL610-301C, TRP160, LWM, ROD500

### Shipping Specifications

EAN	4892210239228
Weight	14.2 kg
Master Carton	16
Dimensions	200 x 67 x 220 mm