

# Hearing Protection

## Disposable ear plugs



### uvex com4-fit

- disposable earplugs with a compact, ergonomic design
- perfect for narrow and smaller ear canals
- suitable for use in high noise environments
- patented x-grip technology reduces pressure on the ear canal and aids easy, hygienic removal
- increased wearing comfort, when worn for extended periods

uvex com4-fit			
<b>Part No.</b>	CF-UC	CF-CD	CF-PB
<b>Design</b>	without cord	with cord	without cord
<b>Standard</b>	AS/NZS 1270	AS/NZS 1270	AS/NZS 1270
<b>SLC80</b>	22 dB, Class 4	22 dB, Class 4	22 dB, Class 4
<b>Colour</b>	orange	orange	orange
<b>Packaging</b>	200 pairs, packed in pairs	100 pairs, packed in pairs	200 pairs, dispenser refill

uvex com4-fit			
<b>Part No.</b>	CF-UC-B	CF-UC-D	
<b>Design</b>	without cord	without cord	
<b>Standard</b>	AS/NZS 1270	AS/NZS 1270	
<b>SLC80</b>	22 dB, Class 4	22 dB, Class 4	
<b>Colour</b>	orange	orange	
<b>Packaging</b>	7000 pairs, bulk pack	500 pairs, for wall dispenser	

SLC80 22 dB, Class 4							
Frequency in Hertz	125	250	500	1000	2000	4000	8000
Mean	20.7	20.1	23.5	24.6	29.6	36.2	36.2
STD. Deviation	7.8	7.8	7.9	5.1	5.3	5.5	6.5
Mean minus SD	12.9	12.2	15.6	19.5	24.3	30.6	29.6



### uvex x-fit

- tapered plug shape ensures natural, pressure free fit – maximising comfort and protection levels
- suitable for use in high noise environments
- patented x-grip technology reduces pressure on the ear canal and aids easy, hygienic removal

uvex x-fit			
<b>Part No.</b>	XF-UC	XF-CD	XF-PB
<b>Design</b>	without cord	with cord	without cord
<b>Standard</b>	AS/NZS 1270	AS/NZS 1270	AS/NZS 1270
<b>SLC80</b>	26 dB, Class 5	26 dB, Class 5	26 dB, Class 5
<b>Colour</b>	lime	lime	lime
<b>Packaging</b>	200 pairs, packed in pairs	100 pairs, packed in pairs	200 pairs, dispenser refill

uvex x-fit			
<b>Part No.</b>	XF-UC-B	XF-UC-D	2112.133
<b>Design</b>	without cord	without cord	without cord
<b>Standard</b>	AS/NZS 1270	AS/NZS 1270	AS/NZS 1270
<b>SLC80</b>	26 dB, Class 5	26 dB, Class 5	26 dB, Class 5
<b>Colour</b>	lime	lime	lime
<b>Packaging</b>	7000 pairs, bulk pack	500 pairs, for wall dispenser	15 pairs, retail pack

SLC80 26 dB, Class 5							
Frequency in Hertz	125	250	500	1000	2000	4000	8000
Mean	26.0	28.2	28.7	29.0	34.6	39.5	42.3
STD. Deviation	8.2	9.6	8.8	6.7	4.6	6.0	8.6
Mean minus SD	17.7	18.6	20.0	22.3	30.1	33.5	33.7