



STOP SEIZE - NICKEL

PRODUCT BULLETIN

Product Description

Stop Seize – Nickel is a heavy duty, high temperature water repelling compound that protects against seizure of metal parts. Stop Seize – Nickel resists corrosion and galling and reduces friction and wear in heavy pressure applications. It is recommended for use with stainless steel and other alloys where a copper based anti-seize compound is unsuitable.

Features and benefits

- Outstanding anti-seize properties in conditions up to 1400°C
- Resists galling of parts, especially stainless steel
- Suitable for ease of assembly and dismantling of metal components
- Specifically designed to withstand highly caustic and corrosive conditions. The solid constituents are chemically inert to concentrated acid and alkaline attack, thus providing maximum protection in this environment
- Remains homogenous during storage and will not harden during service

Recommended Applications

Lubricating and protecting stainless steel fasteners, industrial fasteners and other threaded components, valve assemblies, bushings, flanges, slides, guide pins and spindles.

Technical Data

Appearance : Dark grey coloured paste

Carrier : Non-melting grease

Active ingredients : Nickel, graphite

Consistency : NLGI No 1/2

Temperature range : -18°C to +1400°C

Water solubility : Insoluble

Approximate coverage : 5m²/kg

Storage : Store undercover - 0°C to 40°C

Directions for Use:

Use supplied brush or gloved hand. Clean surface thoroughly and apply with supplied brush.

Precaution

Use in accordance with Material Safety Data Sheet.

Keep out of reach of children. May cause sensitisation by skin contact. Wear protective gloves to protect soiling of skin. Wear suitable protective clothing and eye/ face protection. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre.

Warranty: Devcon will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

Warning: For industrial use only.

ORDERING INFORMATION

Stock No.	Unit Size
19030	0.5 kg Brush Top

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids excludes all other warranties in relation to this product.

DPB 21 August 2007

Australia
ITW Polymers & Fluids Pty Ltd
100 Hassall Street, Wetherill Park, NSW, 2164
Phone: (02) 9757 8800
Fax: (02) 9757 3855

New Zealand
ITW Polymers & Fluids
Unit 2, 38 Trugood Drive, East Tamaki 2013, Auckland
Phone: 09 272 1945
Fax: 09 273 6489