

5060AN Hi Flo Refuelling Drum Pump



January 2023

The 5060AN hi flo refuelling drum pump has low torque, is easy to use and with little effort is capable of delivering up to 110 litres per minute or best in class delivery rates of 1.1 litres per rotation.

Supplied complete with 2.6 metres of antistatic, UV & fuel resistant hose, spout, in built spout holster, 4-piece downtube and new heavy duty bung adaptor, the 5060AN also features a PPR covered handle grip designed to reduce operator fatigue during high volume fuel transfer.

Suitable for the fast and efficient transfer of diesel fuel, petrol, avgas, light oils up to SAE30 and kerosene, the 5060AN incorporates a lockable handle to help minimise the possibility of unauthorised fuel transfer.

SPECIFICATIONS, FEATURES AND BENEFITS

- Low torque, high volume easy to use pump delivers up to 110L/min
- Delivery rates of 1.1 litres per rotation
- Lockable handle minimises the possibility of unauthorised fuel transfer
- PPR covered handle grip reduces operator fatigue
- Rubber seal above the bung adaptor reduces fuel contamination
- Supplied complete with 2.6m of anti-static, UV and fuel resistant hose, spout, in built spout holster, 4-piece downtube, heavy duty bung adaptor
- Steel springs on the hose assembly reduce the possibility of premature hose failure
- Suitable for the transfer of diesel fuel, petrol, Avgas, light oils up to SAE30 and kerosene



www.alemlube.com.au

NSW/ACT (02) 9677 1555

www.alemlube.co.nz