



ANCHOR BOND TOUCH UP PAINT

PRODUCT DESCRIPTION:

Anchor Bond touch up paint is a fast drying, superior quality acrylic spray paint formulated for the maintenance and repair of pre-painted metal surfaces such as *Colorbond® and powder coated finishes. The use of premium grade pigments, polymers and solvents, ensure unparalleled results, excellent coverage and excellent UV stability with long lasting colour qualities.

*Colorbond is the registered trademark of Bluescope Steel

APPLICATIONS: Anchor Bond touch up paint is suitable for use on:

- Metal roofing, gutters, downpipes & fascia's
- Fencing & railings
- Metal garage doors
- Tank Exteriors
- Outdoor Furniture
- Architectural metal work
- Powder coating touch up

SURFACE PREPARATION: Remove all dirt, wax, grease, dust and contaminants from the surface. Remove any loose and flaking paint with wire brush, scraper or mechanical sander. For best results always remove rust back to bare metal. Clean the surface with Pacer P08 Wax & Grease remover and allow to dry thoroughly prior to application. Prime the surface with the appropriate Anchorbond primer.

DIRECTIONS: Cover any adjacent areas to protect from overspray. Shake can vigorously for one minute after the sound of agitator is heard. Spray from a distance of approximately 25cm in an even sweeping motion. For best protection 2-3 coats are recommended. Avoid applying in windy conditions.

DRYING TIMES: at 25°C < 50% RH

TOUCH DRY: 5-7 MINS

RECOAT: 10-15 MINS

Ideal application temperature is 16°C - 25°C.

We recommend doing a test spray if applying at temperatures above 30°C to ensure the desired finish is achieved. Avoid applying in damp conditions.

COVERAGE: Approximately 1.5M² per 300g. Coverage is also dependent on film thickness, atmospheric conditions and spraying technique.

CLEAN UP: Pacer F57 All purpose thinner or mineral turpentine

To clean nozzle after use and prevent blocking turn the can upside down and spray until only the gas escapes.

PACK SIZES: 300G & 150G (not all colours in both sizes)

STORAGE: Store away from sources of ignition, naked flames and direct path of sun and preferably in temperatures range 15°C to 30°C. When stored as specified the product has shelf life of two (2) years minimum.

WARNING: Intentional misuse by deliberately inhaling contents can be harmful or fatal. Do not puncture this container even when empty. Avoid breathing of vapour and mist. Provide adequate ventilation when spraying in confined spaces. Avoid contact with eyes and skin.

HEALTH AND SAFETY: Highly flammable, do not use near fire or open flame. Store in a cool place and out of direct path of the sun. Keep Out of Reach of Children. If swallowed seek medical advice immediately or contact the Poisons Information Center on 13 11 26. Spills and leaks can be contained with absorbent material such as sand, earth or saw dust. Dispose of waste products thoughtfully or through Chemical Waste Disposal Authority.

FIRST AID: Refer to the Safety Data sheet available at www.cwbrands.com.au/

PROPELLANT: blend of Hydrocarbons & Dimethyl Ether.





ANCHOR BOND TOUCH UP PAINT

DISCLAIMER:

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure suitability of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.