

RUBBER PRODUCTS

7093

GST II AIR & WATER - BLACK

Economical and versatile hose for air , water and many agricultural chemicals. The EPDM tube and cover resists heat , sunlight , ozone , weathering. The GST II hose exceeds RMA class C medium oil resistance requirements. Suitable for applications such as oil mist lubricating air lines, but not suitable for the transfer of petroleum products. Closely plied reinforcement of high tensile textile cord provides excellent coupling retention and kink resistance.



ID (mm)	OD (mm)	Working Pressure	Weight (kg/ mtr)	Minimum Bend Radius (mm)	Part Number	Reel Lengths (MTR)
4.8	11.1	200 PSI	0.09	50	7093-19200	228.5
6.4	12.7	200 PSI	0.15	63	7093-25200	228.5
7.9	15.1	200 PSI	0.20	84	7093-31200	213.0
9.5	16.7	200 PSI	0.21	90	7093-38200	20*,198
12.7	20.7	200 PSI	0.32	115	7093-50200	20*,152
15.9	24.6	200 PSI	0.36	140	7093-63200	137
19.1	28.2	200 PSI	0.48	150	7093-75200	20*,106.7
25.4	35.7	200 PSI	0.56	180	7093-100200	76.2

Temp Range	Min -40°C to Max +100°C
Tube	Black , smooth extruded EPDM
Cover	Black , smooth extruded EPDM
Reinforcement	Multiple textile spirals
Ink Branding	White ink print
	PARKER SERIES 7093 GST® II (size) XXX PSI MAX WP MADE IN USA

Packaging	Exact length reels (+15 mt /-0 mt.), 90% 1 pc., 10% 2 pc. - 15 mt min.
-----------	--

*For 20m coils please add -020 where applicable Recommended safety factor 4:1 All W.P. ratings are at 20°C. IHF-7093-001