

DANGER

Causes severe skin burns and eye damage. May be corrosive to metals. Harmful if swallowed. Harmful in contact with skin.
Harmful to aquatic life due to extreme pH.
Contains: Phosphoric Acid, Ammonium bifluoride.

**PREMIER
ONE**

ALUMINIUM BRIGHTENER

Directions:

Clean item of grease and dirt before using Aluminium Brightener. Apply with spray bottle, foam gun or broom. Allow 1-2 minutes and rinse very well with high pressure spray unit or high volume hose.

For fuel tanks, aluminium trays tops and bud wheels, (removing wheel nut covers before applying) mix 1 part Aluminium Brightener to 6 parts water.

Truck Chassis: 1 part to 6 parts water

Tipper Bodies: 1 part to 60 parts water

Note: Owing to a vast range of alloys available, trials should be made to determine the suitability of Aluminium Brightener.

PREMIER ONE PRODUCTS PTY LTD

Unit 10, 11-13 Potter CL, Wetherill Park NSW 2164, Tel: (02) 9756 2419, FAX: (02) 9756 2020

www.premieroneproducts.com.au

PREVENTION

Keep out of reach of children. Avoid breathing fumes, mists, vapours or spray. Do not get in eyes, on skin, or on clothing. Wash contacted areas thoroughly after handling. Use only outdoors or in a well ventilated area. Avoid release to the environment. Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

If eye irritation persists: seek medical attention. Wash with plenty of soap and water. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Not combustible. Use extinguishing media suited to burning materials.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed.

UN Number: 1760

Hazchem Code: 2X

Dangerous Goods Class: Class 8

Packaging Group: III

5lt 20lt 205lt

Additional information is listed in the Material Safety Data Sheet

DANGER

Causes severe skin burns and eye damage. May be corrosive to metals. Harmful if swallowed. Harmful in contact with skin.
Harmful to aquatic life due to extreme pH.
Contains: Phosphoric Acid, Ammonium bifluoride.

**PREMIER
ONE**

ALUMINIUM BRIGHTENER

Directions:

Clean item of grease and dirt before using Aluminium Brightener. Apply with spray bottle, foam gun or broom. Allow 1-2 minutes and rinse very well with high pressure spray unit or high volume hose.

For fuel tanks, aluminium trays tops and bud wheels, (removing wheel nut covers before applying) mix 1 part Aluminium Brightener to 6 parts water.

Truck Chassis: 1 part to 6 parts water

Tipper Bodies: 1 part to 60 parts water

Note: Owing to a vast range of alloys available, trials should be made to determine the suitability of Aluminium Brightener.

PREMIER ONE PRODUCTS PTY LTD

Unit 10, 11-13 Potter CL, Wetherill Park NSW 2164, Tel: (02) 9756 2419, FAX: (02) 9756 2020

www.premieroneproducts.com.au

PREVENTION

Keep out of reach of children. Avoid breathing fumes, mists, vapours or spray. Do not get in eyes, on skin, or on clothing. Wash contacted areas thoroughly after handling. Use only outdoors or in a well ventilated area. Avoid release to the environment. Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

If eye irritation persists: seek medical attention. Wash with plenty of soap and water. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Not combustible. Use extinguishing media suited to burning materials.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed.

UN Number: 1760

Hazchem Code: 2X

Dangerous Goods Class: Class 8

Packaging Group: III

5lt 20lt 205lt

Additional information is listed in the Material Safety Data Sheet